

Low Profile Torque Wrench

LOW series is the professional Low profile hydraulic torque wrench Compare with the square drive hydraulic torque wrench, this series work directly on the nuts, and its body suits well in the Limited space. LOW covers the nuts To ful fill all different working situations, the user can just replace the hexagon cassette because the hexagon cassette is changeable, or add the reducer.

All models available as per your requirement.
Mail us your query and we are ready to serve you.

Technical Data

Model No.	HSL-0.75	HSL-1	HSL-1.5	HSL-2	HSL-4	HSL-8	HSL-16	HSL-32	HSL-45	
Tool Hex mm / inch	From	13 1/2"	'13 1/2"	19 3/4"	19 3/4"	25 1"	50 1.7/8"	65 2.5/8"	80 3.1/8"	80 3.1/8"
	To	41 1.5/8"	41 .5/8"	46 1.5/8"	60 2.3/8"	80 3.1/8"	105 4"	115 4.5/8"	155 6.1/8"	155 6.1/8"
Min Torque N-m (ft) /lbs	55.58(41)	61.0(45)	135.5(100)	260(192)	540 (395)	1125 (830)	2115 (1560)	4365(3220)	6600(4865)	
MAX Torque N-m (ft/lbs)	665 (490)	760 (560)	1350 (995)	2614(1928)	5355(3950)	11700(8630)	22506(16600)	48335(35650)	65595(47380)	
Output Accuracy	+/-3%	+/-3%	+/-3%	+/-3%	+/-3%	+/-3%	+/-3%	+/-3%	+/-3%	
Repeatability	100%	100%	100%	100%	100%	100%	100%	100%	100%	
Duty Cycle	100%	100%	100%	100%	100%	100%	100%	100%	100%	
Corrosion Protection	Standard									
Cylinder Weight Kg / Lbs	0.38/ (0.84)	0.50/ (1.1)	0.55/ (1.2)	1.59 / (3.50)	2.73 / (6.00)	5.32 / (11.70)	7.27 / (16.00)	11.82 / (26.00)	13.7/ (30.2)	
Link Weight Kg / Lbs	From	From	0.47/ (1)	0.50/ (1)	0.60/ (1.3)	1.09 / (2.40)	2.45 / (5.40)	5.41 / (11.90)	9.55 / (21.00)	13.18 / (29.00)
	To	To	0.47/	0.50/	0.90/	1.59 / (3.50)	3.45 / (7.60)	6.59 / (14.50)	12.73 / (2.00)	17.95 / (39.50)